

# Fuzhou ZhuoYuan Machine Co. Ltd

No.888 Jinfeng Road, Gaoxin Zone, Fuzhou City, Jiangxi Province, China

MOB:+86-18779432105

FAX: 0794-8731609

Email: [sales2@rebartyingmachine.com](mailto:sales2@rebartyingmachine.com)

Whatsapp:[+86-18779432105](https://www.whatsapp.com/business/profile/18779432105)

## ECU-controlled rebar tier (CE APPROVAL)

Model No.	WL-210B(Li-ino)	WL-400B(Li-ino)
Max Tying Diameter	21mm	40mm
Voltage & Capacity	DC14.4V(4.4AH)	DC14.4V(4.4AH)
Charge Time	Approx.70mins	Approx.70mins
Tying speed per knot	0.7 seconds	0.75 seconds
Ties per Charge	Over 3200ties	Over 3200 ties
Ties per Coil	Approx. 195ties(3turns)	Approx.130ties(3turns)
Turns per Tie	2turns/3turns	2turns/3turns
Length of Wire for Tying	380mm/2 turns	650mm/2 turns
	550mm/3 turns	750mm/3 turns
Wire Type	Black annealed wire or Galvanized wire	Black annealed wire or Galvanized wire
Net Weight	1.8kgs	1.9kgs
Dimension(L)X(W)X(H)	275mmX120mmX275mm	295mmX120mmX275mm

### Packing Info.

set including:

- . 1Pc Rebar tier machine
  - . 2Pc Battery pack
  - . 1Pc Quick charger
  - . 3Pcs of steel wire rolls
  - . 1Pc Specification
  - . 1pc of Inner Hexagon Spanner
  - . 1pc of Sharp Nose Pliers
- Packing Size: 45×34×13cm  
GW of one set: 7kg

One

.....



Spare Parts for Rebar Tying Machine if you have extra needs.

## Wire (Black annealed wire or Galvanized wire)

<b>Model</b>	WL
<b>Diameter</b>	0.8mm (The thickness of wire is only 0.8mm)
<b>Material</b>	Q195
<b>Length</b>	100m
<b>Packing Info.</b>	50pcs/carton box, 449*310*105 (mm) , 20.5KGS, 0.017CBM
	2500pcs/pallet, 1020*920*1000 (mm),1000KGS, 0.94CBM

## Battery

<b>Model</b>	WL-4SX(Li-ion)
<b>Voltage &amp; Capacity</b>	DC 14.4V(4.4Ah)
<b>Charge Time</b>	Approx. 70 minutes
<b>Dimension (L) X (W) X (H)</b>	95mm*75mm*100mm
<b>Net Weight</b>	480g

## Charger

<b>Model</b>	WL-4A
<b>Charger Voltage</b>	110V-240V
<b>Frequency</b>	50/60HZ
<b>Dimension (L) X (W) X (H)</b>	165mm*115*60mm
<b>Net Weight</b>	490g